

# GENERAC TRAILER SPECIFICATIONS

6" x 2" Tube Frame and Tongue

12" On-Center C-Channel Floor Crossmembers, 16" On-Center Tube Wall Studs

6" Extended Tongue

Braced And Gusseted Walls, 9" x 14" Corner Gussets, 4" x 4" Gussets reinforcing Wall Posts to Frame

16" On-Center Tube Roof Bows

Adjustable 2-5/16" Coupler

Setback 7K Drop Leg Jack

Safety Chains

7-Way RV-Style Molded Plug

Breakaway Switch with Battery

32" x 70" RV Side Door

Aluminum Door Holder

2250 lb. Rated Heavy-Duty Rear Ramp Door with Integrated Transition

Aluminum Fenders

WideTrac Full width interior walls without fender boxes

Torsion Axle(s)

Brakes on Both Axles

Easy Lube Hubs

15" Radial Tires

Aluminum Wheels

Wheel Assembly, 225 75R15 LRD

Rubberized Undercoating

Polyethylene Vapor Barrier

.030 Smooth Aluminum Exterior

Screwless Exterior

Seamless Aluminum Roof w/ 3" Top Trim 3" Bottom Trim

24" ATP Stoneguard w/ Top Trim

Bright Rear Hoop

Flow-Through Scoop Vents

6'6" Interior Height

3/8" Plywood Wall Liner w/ Aluminum H-Trim (Eliminates Stapled Luan Trim)

Flat Front Full Width Interior Wall

ThermoPly Ceiling Liner (Above roof bows)

3/4" Engineered Wood Floor

(2) 12 Volt Ceiling Mounted LED Dome Lights w/ 1 Wall Switch

LED 6" Oval Tail Lights w/Rubber Mounted

3/4" Bullet Marker Lights (All Clear Lens)

Integrated Backup Lights

Limited 3-Year Warranty

## **Additional Included Options:**

Color Option, White (Standard Color)

Backup Lights, L.E.D.

Transition Plate, Steel for 7 Wide 66 IN From ramp door to trailer floor

Roof Vent, Non Powered 14 x 14 (1 in restroom and 1 for rear of trailer)

Tongue Mounted Hazard Cone Holder

High Security Bar Lock Hasp (Pair)

Steel Wheels in Lieu of Alum Wheels (Black in color)

Add Spare Tire - Aluminum (Black Steel to match trailer wheels)

Spare Tire Mount Exterior-Enclosed

HD 7K (Scissor) Stabilizer Jacks (Scissor Style, 1 on each corner of trailer)

Wheel Chock Holders with Chock\*

Partition Wall with Interior Door (Starting at front of side door)

Ramp Grab Handle, Aluminum (For Side Door)

RV Pull-Out Single Steel Step

**\*Wheel Chock** - Mount (1) on each side of tongue approx. 12" in from outside edge.

Must use chock with grab handle. QTY4 Wheel Chocks. Others mounted in the center.

**U.S. UPFITTERS**  
TRUCK AND VAN EQUIPMENT

a division of **Driverge**